

PCT/GB2004/003652



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

REC'D. 15 NOV 2004

WIPO

PCT

**Bescheinigung**

**Certificate**

**Attestation**

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

**Patentanmeldung Nr.    Patent application No.    Demande de brevet n°**

03255421.4

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

**BEST AVAILABLE COPY**

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

**R C van Dijk**



Anmeldung Nr:  
Application no.: 03255421.4  
Demande no:

Anmeldetag:  
Date of filing: 29.08.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

BAE Systems PLC  
6 Carlton Gardens  
London SW1Y 5AD  
GRANDE BRETAGNE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Retroreflective devices

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:


G02B5/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

XA1807

1

RETROREFLECTIVE DEVICES

This invention relates to retroreflective devices; the term "retroreflective devices" as used herein being intended to encompass generally optical components used for returning radiation automatically from a remote location toward an optical source.

Retroreflective devices are designed to reflect radiation back towards its source, and such devices are thus frequently used to return radiation toward radiating optical sources when it is inconvenient or undesirable to actively generate radiation at locations, remote from the optical sources, which need to send response radiation to fixed or mobile base locations at which the radiating optical sources are sited. Common examples include the use of special reflective materials for safety clothing or signage, cat's eye markers in road surfaces, and measurement points in land surveying or robotic machinery. Retroreflective devices may also be used in combination with optical modulation mechanisms in order to establish two-way optical communication between the base station and the remote location without needing an optical source at the remote end of the link.

Retroreflective devices currently in common use can be classified into two main types.

The first of these accomplishes retroreflection without any focusing of the incoming radiation from the source. This type is commonly available as a component with a set of three mutually perpendicular reflecting surfaces, and is known as a "corner-cube" retroreflector. Different embodiments of this type of reflector exist, but all require very high quality in the reflecting surfaces, which also need to be very accurately assembled in order to provide precise angular coincidence between the incident and reflected beams. Consequently, such components are expensive to make, but they have the advantage of providing diffraction limited performance which gives excellent quality to the reflected beam. Disadvantageously, however, such devices exhibit a limited field of view which varies with the construction details, but which cannot allow coverage of arbitrary angles of incidence across a full hemisphere without grouping several

XA1807

2

reflectors together, where each reflector is pointed in a different direction. This increases the expense and the complexity of constructing such devices with high field of view.

The second type of retroreflective device currently in common use  
5 employs focusing of the incident radiation onto a primary reflecting surface. This type is known as a "cat's eye" retroreflector, and commonly employs glass spheres, or cemented hemispheres, in order to provide retroreflection for paraxial incident rays. Such devices can be made very small (for example with sub-millimetre diameters) and offer a very wide field of view, including a complete  
10 hemisphere or more in a single component. Furthermore, single spheres can be manufactured in quantity at low cost. The main disadvantage of this design is that the reflected radiation is subject to severe spherical aberration for non-paraxial rays, and this can strongly reduce the far-field intensity of the reflected beam measured on-axis. It also leads to significant beam divergence, making the reflection visible far from the axis, which can be undesirable in some  
15 applications, for example in free-space communication where privacy is desired.

A class of lenses, called 'graded refractive index' (or GRIN) lenses, is known, in which the material of the lens exhibits gradual variations in refractive index through its volume. An example is the so-called "GRIN-rod" lens, which  
20 is a graded-index lens with cylindrical symmetry and radial parabolic index distribution. See S. Nemoto and J. Kida, 'Retroreflector using gradient-index rods' Appl. Opt. 30(7), 1 Mar 1991, p.815-822.

In a publication entitled "Gradient Index Optics" published by Academic Press in 1978, E.W. Marchand describes at pages 2 and 3 a lens, previously  
25 discovered by Luneburg, having an index function with spherical symmetry about a point. Marchand describes the Luneburg lens as difficult to make (at least for radiation in the visible region of the spectrum), and goes on to say that the lens, even if it can be made, has limited possibilities for useful application, though he does suggest a possible modification of the lens, incorporating a  
30 mirror to produce an action similar to that of a corner cube.

Sphere lenses with refractive index distributions possessing spherical symmetry are known as 'GRIN-sphere' lenses, having a spherically symmetric

XA1807

3

refractive index distribution in which the refractive index varies gradually across a radial cross-section. Such lenses are known to exhibit improved spherical aberration compared to uniform sphere lenses. See Y. Koike, A. Kanemitsu, Y. Shioda, E. Nihei and Y. Ohtsuka, 'Spherical gradient-index polymer lens with  
5 low spherical aberration' Appl. Opt. 33(17), 1 Jun 1994, p. 3394-3400.

GRIN-rod lenses have been proposed for use in retroreflective devices, but these lenses suffer from restrictions on field of view similar to those exhibited by corner-cube retroreflectors. Other types of cat's eye retroreflector can be based on catadioptric lens designs, but these also share the  
10 aforementioned restrictions on field of view.

The present invention aims to address at least one of the above-identified disadvantages associated with the retroreflective devices currently in common use. Preferred embodiments of the invention aim to overcome, or at least reduce, the spherical aberration experienced in cat's eye retroreflectors based on  
15 conventional sphere lenses while retaining, at least in substantial measure, their benefits of wide field of view compared to corner-cube retroreflectors.

According to one aspect of the invention there is provided a retroreflective device comprising a substantially spherical graded refractive index lens, a reflective part for retroreflecting a radiation beam passing through the  
20 graded refractive index lens and, at least partially surrounding the lens, a non-gaseous transparent material having a substantially uniform refractive index.

The provision of a transparent material of substantially uniform refractive index outside the lens provides for increased ease of manufacture of the device when the refractive index of the refractive material is substantially greater than  
25 unity. The GRIN-sphere lens can then have a refractive index variation which need not be as large as would otherwise be required. Further, by use of the present invention, the refractive index at the outer surface of the lens need not be matched to that of an air interface, which is practically impossible, particularly in the visible and infra-red regions of the spectrum, in which the present invention  
30 has particular application.

Preferably, the refractive index distribution of the GRIN-sphere lens has a spherical aberration reducing effect. The invention may be employed where the

XA1807

4

focusing action of a low-aberration sphere in air is not strong enough to provide convergence of the incident beam to a point on the rear surface of the sphere itself, or if sufficiently low aberration for a particular application cannot be achieved using a GRIN-sphere in air.

5 In preferred embodiments, the transparent material surrounds a substantial part of the lens. In a particularly preferred embodiment, the transparent material surrounds at least approximately one half of the lens, and more preferably surrounds substantially the entire lens.

Note that, herein, the term "spherical" is intended to refer to surfaces  
10 which include both whole spheres and part-spherical surfaces.

The boundary of the transparent material remote from the lens is, in some preferred embodiments of the invention, defined by a substantially spherical surface and in other preferred embodiments the boundary is defined by a substantially planar surface; although any configuration of the boundary can be  
15 used if selected to perform a particular optical purpose.

In order that the invention may be clearly understood and readily carried into effect, some embodiments thereof will now be described, by way of example only, with reference to the accompanying drawings, of which:

Figure 1 shows a retroreflective device in accordance with a first  
20 embodiment of the invention;

Figure 2 shows a retroreflective device in accordance with a second embodiment of the invention;

Figure 3 shows a retroreflective device in accordance with a third embodiment of the invention; and

25 Figure 4 shows two exemplary refractive index distributions in accordance with embodiments of the invention.

Referring now to Figures 1 to 3 of the drawings, preferred embodiments of retroreflective devices based on GRIN-sphere lenses are described, by way of example, but it will be appreciated by those skilled in the art that other designs  
30 may readily be devised to suit particular objectives.

Figure 1 shows a first embodiment of a retroreflective device based on a GRIN-sphere lens arranged in accordance with the invention. The upper

XA1807

5

hemisphere of the mechanical surface of the GRIN-sphere lens 2, shown as a solid circle 2, is the surface through which an incident radiation beam B (which is assumed to be a parallel beam) passes into the GRIN-sphere lens.

In order to improve the optical characteristics of the device, the GRIN-sphere lens 2 is clad in, or otherwise coated with, a transparent material 4 having a uniform refractive index of a particular, desired value. The transparent material has a uniform thickness, and has an outer spherical surface which is arranged concentric with the outer surface of the GRIN-sphere lens 2. The upper surface of the transparent material forms the entrance face of the device. Although not shown in Figure 1, the entrance face of the transparent material 4 (and indeed the equivalent surfaces shown in other figures hereof) may be provided with an anti-reflective coating, applied in any convenient manner.

A reflective coating 6 is applied directly to the outer surface of the transparent material 4, on the side opposite the entrance face, to provide retroreflection of the incident rays 4 as shown. For optimum field of view, the reflective coating 6 covers approximately a hemisphere on the outer surface.

The lens 2 may be made of suitable polymer materials, such as benzyl methacrylate or similar materials, or glass. The desired refractive index distribution may be obtained by any known technique, such as diffusion of suitable materials within the sphere, or photo-inscription in photosensitive material using, for example, ultra-violet sources.

The transparent material 4 may be made of a suitable plastic, for example polymethyl methacrylate, or glass.

The reflective coating 6 may be metallic, for example aluminium, to provide broad spectral reflection, or can itself be of multi-layer design to provide wavelength selective reflection.

A second embodiment of the invention is shown in Figure 2. Here, components similar to that shown in Figure 1 are given the same reference numerals, incremented by 100. The GRIN-sphere lens 102 is immersed in, and may be at least partially supported by, an environment comprising a transparent solid material 104 of uniform refractive index, having a chosen relationship with the refractive index at the GRIN-sphere surface. The transparent material may be

XA1807

6

supported by a solid structure 108, which may for example have a lower surface formed, for example as a planar surface, so as to stably support the device in a preferred orientation on a horizontal surface.

Alternatively, depending for example upon the use for which the device is intended and/or the treatment to which it may be subjected, the lens may be immersed in a transparent liquid material and supported by thin filaments (not shown) stretched from the supporting structure 108.

The entrance face 110 of the transparent material 104, forming a boundary of the transparent material remote from the lens 102, and through which a radiation beam passes to be retroreflected, is in this embodiment defined by a substantially planar surface. Such a form of entrance face is relatively easy to manufacture, and does not require precise alignment with respect to the GRIN-sphere lens 202. However, such a form of entrance face suffers from angularly-dependent retroreflectivity and polarisation effects.

Figure 3 shows a third embodiment of the invention, which reduces angularly-dependent retroreflectivity and polarisation effects. Here, components similar to those previously described have the same reference numerals, incremented by 100. The transparent material 204 is given a hemispherical outer shape. The material may in this embodiment be protected by a transparent optical dome casing (not shown) made of a relatively hard material, such as glass. This arrangement reduces the variation of reflection performance with incidence angle, compared to the embodiment shown in Figure 2. The rays encountering the GRIN-sphere can be made effectively paraxial with respect to the lens formed by the outer surface 210, provided that the radius of curvature of the outer surface is made sufficiently large compared to the radius of the outer surface of the GRIN-sphere lens 202. Due to the preferred relatively large radius of curvature of the outer surface of the transparent material 204 at the entrance face 210, the reflective surface of the reflective material 206 has a smaller radius of curvature than that of the entrance face 210.

Figure 4 shows two exemplary refractive index distributions of the GRIN-sphere lens, which may be used in any of the first to third embodiments of the invention.



XA1807

7

The distributions are plotted across the entire (normalised) radius of the GRIN-sphere lens, ranging from 0 to 1. The refractive index of the GRIN-sphere lens at each radial point is normalised with respect to the refractive index of the transparent material. In the lower one of the two illustrated distributions, the refractive index ranges from a minimum of approximately 1.02 near the outer surface of the GRIN-sphere lens to approximately 1.10 at the centre of the GRIN sphere lens. In the upper one of the two illustrated distributions, the refractive index ranges from a minimum of approximately 1.08 near the outer surface of the GRIN-sphere lens to approximately 1.14 at the centre of the GRIN sphere lens.

Each of the two exemplary refractive index distributions includes parts having at least two separate radial extents within which the material of the GRIN-sphere lens has a continuously varying refractive index, the refractive index variation having a gradient discontinuity between the two radial extents. The discontinuity is the minimum shown near the outer surface of the lens.

Each of the two exemplary refractive index distributions provides a GRIN-sphere lens having a refractive index at its centre which is greater than a refractive index at its outer surface. Further, it can be seen that the transparent material has a refractive index which is less than a refractive index of GRIN-sphere lens at its outer surface.

Preferably, the ratio of the refractive index of GRIN-sphere lens at its outer surface to the refractive index of the transparent material is between 1 and 2, for example between 1.02 and 1.2. Further preferably, the ratio of the refractive index of GRIN-sphere lens at its centre to the refractive index of the transparent material is between 1 and 2, for example between 1.05 and 1.5.

Typically, in embodiments of the invention, the GRIN-sphere lens has a refractive index distribution which averages, across a radial cross-section, between 1.4 and 1.8, and the transparent material has a refractive index greater than 1.3.

The transparent material as described in each of the above embodiments is preferably formed, for example as two interfitting halves, by a moulding process. In this manner, the material can be accurately shaped to support the GRIN-sphere lens concentrically with respect to its inner and outer spherical

XA1807

8


surfaces. Alternative procedures may of course be used depending upon various criteria, such as overall dimensions, performance requirements and operational demands such as robustness.

The above embodiments are to be understood as illustrative examples of the invention. It is to be understood that any feature described in relation to any one embodiment may be used alone, or in combination with other features described, and may also be used in combination with one or more features of any other of the embodiments, or any combination of any other of the embodiments. Furthermore, equivalents and modifications not described above may also be employed without departing from the scope of the invention, which is defined in the accompanying claims.

XA1807

9

## CLAIMS



1. A retroreflective device comprising a substantially spherical graded refractive index lens, a reflective part for retroreflecting a radiation beam  
5 passing through the graded refractive index lens and, at least partially surrounding the lens, a non-gaseous transparent material having a substantially uniform refractive index.

2. A device according to claim 1, wherein said graded refractive  
10 index lens has a gradually varying, spherically symmetric, refractive index distribution.

3. A device according to claim 2, wherein said refractive index distribution includes parts having at least two separate radial extents within  
15 which the material of the lens has a continuously varying refractive index, the refractive index variation having a gradient discontinuity between said two radial extents.

4. A device according to any preceding claim, wherein said graded  
20 refractive index lens has a refractive index at its centre which is greater than a refractive index at its outer surface.

5. A device according to any preceding claim, wherein said transparent material has a refractive index which is less than a refractive index of  
25 said graded refractive index lens at its outer surface.

6. A device according to any preceding claim, wherein a ratio of the refractive index of said graded refractive index lens at its outer surface to a refractive index of said transparent material is between 1 and 2.

30

XA1807

10

7. A device according to any preceding claim, wherein a ratio of the refractive index of said graded refractive index lens at its centre to a refractive index of said transparent material is between 1 and 2.

5 8. A device according to any preceding claim, wherein said transparent material surrounds at least approximately one half of the lens.

9. A device according to any preceding claim, wherein at least part of said transparent material is located between said graded refractive index lens and  
10 the reflective part.

10. A device according to any preceding claim, wherein said reflective part includes a substantially spherical reflective surface arranged concentrically with respect to said graded refractive index lens.

15

15

11. A device according to any preceding claim, wherein a boundary of the transparent material remote from said lens, and through which a radiation beam passes to be retroreflected, is defined by a substantially spherical transparent surface arranged concentrically with respect to the graded refractive  
20 index lens.

12. A device according to claim 10 and 11, wherein said substantially spherical reflective surface and substantially spherical transparent surface have substantially the same radius of curvature.

25

13. A device according to claim 10 and 11, wherein said substantially spherical reflective surface and substantially spherical transparent surface have different radii of curvature.

30 14. A device according to claim 13, wherein said substantially spherical reflective surface has a smaller radius of curvature than that of said substantially spherical transparent surface.

XA1807

11

15. A device according to any of claims 1 to 10, wherein a boundary of the transparent material remote from said lens, and through which a radiation beam passes to be retroreflected, is defined by a substantially planar surface.

5

16. A device according to any preceding claim, wherein said transparent material comprises a solid moulded component.

17. A device according to any preceding claim, wherein said  
10 transparent material has a refractive index greater than 1.3.

18. A device according to any preceding claim, wherein said graded refractive index lens has a refractive index distribution which averages, across a radial cross-section, between 1.4 and 1.8.


15

2003 AUG 29 17:32

XA1807

12


ABSTRACT




RETROREFLECTIVE DEVICES AND SYSTEMS

5        A retroreflective device comprising a substantially spherical graded refractive index lens, referred to as a GRIN-sphere lens, a reflective part for retroreflecting a radiation beam passing through the graded refractive index lens and, at least partially surrounding the lens, a transparent material having a substantially uniform refractive index.

10




1/4



**Fig. 1**

2/4



**Fig. 2**



3/4





Fig. 3

4/4

**Fig. 4**

GB2004/003652



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**